



**WACKER  
NEUSON**  
*all it takes!*

# Dumpers

Wheeled and Dual View



## Material movers

Articulated wheeled dumpers are excellent for moving bulk materials. The smaller foot print allows dumpers to maneuver around confined and busy job sites, moving materials faster and significantly improving cycle times.



## Always facing the task

With our Dual View dumpers, the operator can quickly and comfortably change the seat and console position to keep the task front and center. The entire operating platform rotates 180 degrees, giving the best view while working or driving the machine.

## Performance Data

	Unit	DW30	DW30 Concrete edition	DW50
Max. operating power at operating speed	hp rpm	45.3 @ 2,200	45.3 @ 2,200	59.7 @ 2,300
Engine type		Perkins 403J-E17T, liquid-cooled, 3-cylinder turbo diesel engine.		Deutz TD 2.2, liquid-cooled, 3-cylinder turbo diesel engine.
Fuel tank capacity	gal	11.9	11.9	15.9
Travel speed	mph	0-15.5	0-15.5	0-15.5
Standard tires		11.50/80 x 15.3, Mitas tractor tread		12.5-18/16, Mitas universal tread
Final drive		Hydrostatic transmission, permanent 4-wheel drive, electronic driving direction switch.		
Working brake		Hydrostatic / Wet multidisk		
Pump capacity Operating / Drive	gal/min	8.2 / 26.2	8.2 / 26.2	14 / 32.5
Operating pressure Operating / Drive	psi	2,901 / 6,498	2,901 / 6,498	3,191 / 7,252
Hydraulic tank capacity	gal	11.1	11.1	10.6
Height ROPS/CAB	in	112.6 / 105.1	112.6 / -	110.8 / -
Width	in	70.1	70.1	75.8
Length	in	166.3	199.3	177.0
Max safe payload	lb	6,614	6,614	11,023
Skip capacity	leveled heaped water	yd <sup>3</sup> yd <sup>3</sup> gal	1.67 2.29 262	2.62 3.47 3.49
Transport weight ROPS / CAB	lbs	5,545 / 5,895	5,675 / -	7,580 / -

## Performance

- Hydrostatic drive offers simple, intuitive operation. The four-wheel drive provides perfect traction on difficult terrain and articulated steering allows for a tight turning radius

## Efficiency

- Heavy-duty, impact resistant swivel skip allows material to be unloaded from the front or either side, making dumping more precise and efficient

## Maintenance

- Extended maintenance intervals of 500 operating hours provides additional cost savings



## Dual View Dumpers

		Unit	DV60	DV90	DV100
Max. operating power at operating speed		hp rpm	74.2 @ 2,200	74.2 @ 2,200	74.2 @ 2,200
Engine type			Deutz TD2.9 L4, liquid-cooled, 4-cylinder, diesel engine.		
Fuel tank capacity		gal	21.1	21.1	21.1
Travel speed		mph	0-18.6	0-18.6	0-18.6
Standard tires			405/10-20, Mitas universal tread	500/60-22.5, Mitas universal tread	
Turning radius outside		in	232.7	252.4	257.8
Final drive			Hydrostatic transmission, permanent 4-wheel drive, electronic driving direction switch.		
Working brake			Hydrostatic / Wet multidisk		
Pump capacity Operating / Drive		psi	16.1 / 32.6	16.1 / 32.6	16.1 / 32.6
Operating pressure Operating / Drive		gal	3,481 / 3,771	3,481 / 3,771	3,481 / 3,771
Hydraulic tank capacity		gal	15.9	15.9	15.9
Height ROPS/CAB		in	130 / 115.7	- / 115.9	- / 115.9
Width		in	87.3	96.6	99.4
Max safe payload		lb	13,228	19,841	22,046
Skip capacity	leveled	yd <sup>3</sup>	3.0	4.3	5.4
	heaped	yd <sup>3</sup>	4.1	5.7	6.5
	water	gal	423	542	674
Transport weight ROPS / CAB		lbs	9,524 / 10,229	11,144 / 11,607	10,483 / 10,946

